

## JA494 棱线发射器 螺丝表 The Drawn Line Blaster

| 袋子编号<br>Bag No. | 包装数量<br>Give Qty | Parts Name                             | 规格<br>Spec.  | 使用数量<br>Actual use Qty |
|-----------------|------------------|--|--------------|------------------------|
| 1               | 2                | Ball Detent                            | D6x7 15N     | 2                      |
|                 | 3                | Hex Socket Cap Screw                   | M3*20        | 2                      |
|                 | 3                | Allen Key                              | 2.5mm        | 2                      |
|                 | 3                | Allen Key                              | 4mm          | 2                      |
|                 | 1                | Brass Knurled Heat-Set Threaded Insert | M3*3*4.5     | 1                      |
|                 | 17               | Hex Socket Cap Screw                   | M3*10        | 15                     |
|                 | 5                | Round Head Cotter Pin                  | M2*10        | 4                      |
|                 | 2                | Bearing                                | 3*7*3        | 2                      |
|                 | 1                | Dowel Pin                              | M3*10        | 1                      |
|                 | 2                | Dowel Pin                              | M3*20        | 1                      |
|                 | 1                | U625 Bearing                           | U625(5-20-7) | 1                      |
|                 | 5                | M3 Antislip nut                        | M3 (5.5-4)   | 4                      |
|                 | 3                | Hex Socket Cap Screw                   | M5*25        | 3                      |

|   |   |                    |           |   |
|---|---|--------------------|-----------|---|
| 2 | 2 | Compression Spring | 0.4*4*15  | 1 |
|   | 4 | Black O-Ring       | 11*2      | 2 |
|   | 4 | Black O-Ring       | 29*2.4    | 2 |
|   | 5 | Red O-Ring         | 19*2      | 3 |
|   | 1 | Silicon Pad        | 28-18-2.5 | 1 |
|   | 1 | Optic Fibre        | 30MM      | 1 |

|   |   |                   |                     |   |
|---|---|-------------------|---------------------|---|
| 3 | 1 | Nylon String      | 2mm wire, 1m length | 1 |
|   | 2 | Aluminium Rod     | 280*10*3            | 2 |
|   | 1 | Lubricatant       | 25ml                | 1 |
|   | 1 | PC Tube           | 120*32*1.5          | 1 |
|   | 2 | Double-Ended Stud | M3*180              | 2 |
|   | 1 | Main Spring       | 11.0KG              | 1 |
|   | 1 | Aluminium Tube    | 20CM                | 1 |